Technický list 21.08.25 - 16:31





Easyfit spring check valve with female ends for solvent welding, ASTM series

The SSE Easyfit check valve with spring loaded shutter developed with Giugiaro Design stands out for the innovative installation method that guarantees reliable service over time. This valve is also equipped with a customising Labelling System.

- Customisable Labelling System: built-in LCE module on the valve body made up of transparent protection plug and customisable tag holder using the LSE set (available as accessory). The customisation potential lets you identify the valve on the system according to specific needs.
- Ideal for horizontal installations: perfect seal even with low back pressure. Silent and durable even with strong vibrations and pulsating
- PVC-C shutter and springs available made of STAINLESS steel 316, Hastelloy C276, A316 PTFE encapsulated: maximum reliability in a
 wide field of applications from salt water to aggressive acids
- · Connection system for solvent weld and threaded joints
- Valve material compatibility (PVC-C) with water conveyance, drinking water and other food substances according to current regulations
- PN16 True Union valve body made for PVC-C injection moulding and European Directive 2014/68/EU (PED) compliant for pressurised equipment. ISO 9393 compliant test requirements
- Short face to face dimension according to international regulation ISO 7508 series III "short" and fully interchangeable with VXE DN 10÷50 ball valve models
- · Union nuts with rack for tightening adjustment via Easyfit handle or via Easyforque adjustment kit (available as accessories)
- · Can be installed in either a vertical or horizontal position





