M9.00.PX - M9.00.WX

2-Wires Flow Monitor and Transmitter



Objednací číslo	product.detail.attribute.Mounting	product.detail.attribute.Power supply	product.detail.attribute.Wire power Technology	product.detail.attribute.Sensor Input
M9.00.P1	Panel	12 - 24 VCC	2 wire	Flow (Frequency)
M9.00.W1	Wall	12 - 24 VCC	2 wire	Flow (Frequency)
M9.00.W2	Wall	110 - 230 VCA	2 wire	Flow (Frequency)

M9.00.PX - M9.00.WX

FLS M9.00 is a powerful flow monitor based on 2-wire technology designed to convert the frequency signal of FLS flow sensors into a flow rate. M9.00 is equipped with a wide 4" display which shows measured values clearly. Moreover the standard backlight improves further the display visibility. The first procedure will grant a easy set up of main parameters. A flow rate reference can be used for a recalibration or a alignment through a intuitive "in-line calibration". A 2 wires 4-20mA output combined with a solid state relay allow to remote instant flow rate as well as an alarm.

- APPLICATIONS • Water treatment systems • Industrial waste water treatment and recovery • Water distribution • Filtration systems • Swimming pools & SPA • Irrigation & Fertigation • Leak detection MAIN FEATURES • Wide display • Bright backlight • Installation flexibility • Solid State Relays for programmable alarms • Multilanguage menu • USB port for software updating