

M9.03.PX – M9.03.WX

Dual Flow Monitor and Transmitter



Objednáací číslo	product.detail.attribute.Mounting	product.detail.attribute.Power supply	product.detail.attribute.Wire power Technology	product.detail.attribute.Sensor Input
M9.03.P1	Panel	12 – 24 VCC	3/4 wire	2* Flow (Frequency)
M9.03.W1	Wall	12 – 24 VCC	3/4 wire	2* Flow (Frequency)
M9.03.W2	Wall	110 – 230 VCA	3/4 wire	2* Flow (Frequency)

M9.03.PX – M9.03.WX

FLS M9.03 is a powerful dual flow monitor designed to convert the frequency signals of FLS flow sensors into flow rates. M9.03 is equipped with a 4" wide full graphic display which shows measured values clearly and a lot of other useful information. Moreover, due to a multicolor display plus a powerful backlight, measurement status can be determined easily from afar also. A tutorial software guarantees a mistake-proof and fast set up of every parameters. Calibrations can be performed just fixing installation features or using a reference value through a new "in-line calibration". Two 4-20mA output are available to remote each flow rate to an external device. A proper combination of digital outputs allows customized setups for any process to be controlled. The USB port on the rear part allows the upgrade of software offering a wide range of customization services both standard and on request.

- APPLICATIONS • Water treatment systems • Industrial waste water treatment and recovery • Water distribution • Filtration systems • Swimming pools & SPA • Irrigation & Fertigation • Leak detection • Cooling water monitoring • Processing and manufacturing industry • Chemical production
- MAIN FEATURES • Wide full graphic display • Multicolor backlight • Help on board • Delta flow rates visualization • Fast, intuitive and mistake-proof calibration software • Mechanical relays for external device control • Solid State Relays for programmable alarms • Multilanguage menu • USB port for software upgrading