



C150

Epoxy Body Conductivity Sensor with Graphite Electrodes with Temperature Sensor (Pt100) included



Objednací číslo	product.detail.attribute.Description	product.detail.attribute.Applications/ Flow Rate Range	product.detail.attribute.Cell Constant	product.detail.attribute
C150.01TC	Pt100 included	0.1 [CS:Simbolo:μ]S/cm to 2000 [CS:Simbolo:μ]S/cm \$ (10M[CS:Simbolo:Ω] to 500M[CS:Simbolo:Ω] *cm)	0,1	5 m (16,5 ft.)
C150.1TC	Pt100 included	0.1 [CS:Simbolo:μ]S/cm to 2000 [CS:Simbolo:μ]S/cm	1,0	5 m (16,5 ft.)



C150

- APPLICATIONS • Chemical concentrations • Foods industry • Steam generation • Metal finishing and mining • Textile industry • Pulp and paper • Water treatment • Reverse osmosis • Softener regeneration • De-ionization • Distillation • Aquaculture • Agriculture and fertilizing systems MAIN FEATURES • Graphite or Platinum measuring surfaces • Suitable for laboratory, industrial or portable applications so long as liquid is filtered • In line and submersion installation • Temperature sensor included • Cell constant choices of 0.1 and 10