

C100

PP Body Conductivity Sensor with SS Electrodes with Temperature Sensor (Pt100) included



Objednací číslo	product.detail.attribute.Description	product.detail.attribute.Application/ Flow Rate Range	product.detail.attribute.Cell Constant	product.detail.attribute.
C100.01TC	Pt100 included	0.1 [CS:Simbolo:μ]S/cm to 2000 [CS:Simbolo:μ]S/cm (10M[CS:Simbolo:Ω] to 500M[CS:Simbolo:Ω] *cm)	0,1	4 poles connector
C100.02TC	Pt100 included	0.2 [CS:Simbolo:μ]S/cm to 4000 [CS:Simbolo:μ]S/cm	0,2	4 poles connector
C100.1TC	Pt100 included	1 [CS:Simbolo:μ]S/cm to 20000 [CS:Simbolo:μ]S/cm	1	4 poles connector

C100

- APPLICATIONS • Agriculture and fertilizing system • Water treatment • Foods industry • Aquaculture • Ultrapure water application: production and use MAIN FEATURES • Stainless steel measuring surfaces • Considerable ratio performance/price • Temperature sensor included • Wide range of cell constant • Rugged sensor body in PP (C100) • Sensor in SS completely (C300) • C300.001TCCK with certified cell constant