

C300

SS Body and Electrodes Conductivity Sensors with Temperature Sensor (Pt1000) included



Objednací číslo	product.detail.attribute.Description	product.detail.attribute.Applicazioni/ Flow Rate Range	product.detail.attribute.Cell Constant	product.detail.attr
C300.001.TCCK	Simplified Cell constant	0.55 [CS:Simbolo:μ]S/cm to 200 [CS:Simbolo:μ]S/cm (18,2M[CS:Simbolo:Ω] to 5K[CS:Simbolo:Ω] *cm)	0,01	3 m
C300.001TC	-	0.55 [CS:Simbolo:μ]S/cm to 200 [CS:Simbolo:μ]S/cm (18,2M[CS:Simbolo:Ω] to 5K[CS:Simbolo:Ω] *cm)	0,01	3 m
C300.10TC	-	10 [CS:Simbolo:μ]S/cm to 200000 [CS:Simbolo:μ]S/cm	10	3 m

C300

- APPLICATIONS • Agriculture and fertilizing system • Water treatment • Foods industry • Aquaculture • Ultrapure water application: production and use MAIN FEATURES • Stainless steel measuring surfaces • Considerable ratio performance/price • Temperature sensor included • Wide range of cell constant • Rugged sensor body in PP (C100) • Sensor in SS completely (C300) • C300.001TCCK with certified cell constant