

# C200

Epoxy Body Conductivity Sensor with Platinum Electrodes with Temperature Sensor (Pt100) included



Objednací číslo	Materiál	Kategorie	product.detail.attribute.family	Série	product.detail.attribute.Description	product.detail.Flow Rate Range
C200.01TC	FLS Measurement Instrumentation	FLS systém pro měření a regulaci	ph / ORP / pressure-level Electrodes	Potenciometry a indukční senzory vodivosti	Pt100 included	0.1 [CS:Simbolo;μ]§ (10M[CS:Simbol 500M[CS:Simb
C200.10TC	FLS Measurement Instrumentation	FLS systém pro měření a regulaci	ph / ORP / pressure-level Electrodes	Potenciometry a indukční senzory vodivosti	Pt100 included	0.1 [CS:Simbolo;μ]§
C200.ITC	FLS Measurement Instrumentation	FLS systém pro měření a regulaci	ph / ORP / pressure-level Electrodes	Potenciometry a indukční senzory vodivosti	Pt100 included	0.1 [CS:Simbolo;μ]§

## C200

- APPLICATIONS • Chemical concentrations • Foods industry • Steam generation • Metal finishing and mining • Textile industry • Pulp and paper • Water treatment • Reverse osmosis • Softener regeneration • De-ionization • Distillation • Aquaculture • Agriculture and fertilizing systems MAIN FEATURES • Graphite or Platinum measuring surfaces • Suitable for laboratory, industrial or portable applications so long as liquid is filtered • In line and submersion installation • Temperature sensor included • Cell constant choices of 0.1 and 10